

Analogue drying ovens



DO-90

Features

- Natural air convection.
- Adjustable temperature from 40° C to 250° C.
- Temperature regulation by hydraulic thermostat
- Homogeneity and stability according to DIN-12880.
- Safety according to EN-61010-1, EN-61010-2-010.
- Heating by electric resistance, assembled in independent chamber, allowing an optimal stabilization of temperature.
- External case epoxy resin painted.
- Inner chamber, inner side door and trays made in stainless steel AISI 304.
- Silicone sealing gasket.
- Adjustable aeration device.

Supplied with:

- Two perforated trays made in stainless steel AISI 304 adjustable in height.

Analogue drying ovens

Reference	Capacity	Temp Stab /Homog	Int. H x W x D in mm	Ext. H x W x D in mm	Power W	Weight kg.
DO-20	20 l.	± 0,5 % / ± 2 %	300 X 250 X 250	610 X 440 X 400	600	27
DO-40	40 l.	± 0,5 % / ± 2 %	400 X 350 X 300	710 X 540 X 450	900	40
DO-50	50 l.	± 0,5 % / ± 2 %	330 X 470 X 330	645 X 665 X 480	1000	45
DO-90	90 l.	± 0,5 % / ± 2 %	500 X 450 X 400	810 X 640 X 550	1200	54
DO-150	150 l.	± 0,5 % / ± 2 %	500 X 600 X 500	810 X 790 X 650	2000	70

Accessories

Stainless steel perforated shelves

Reference	For incubators	Nº max. shelves/incubator
BE-20	DO-20, DOD 20	5
BE-40	DO-40, DOD 40	7
BE-50	DO-50, DOD 50	6
BE-90	DO-90, DOD 90	9
BE-150	DO-150, DOD 150	9

