

**INCUBATORS, BACTERIOLOGICAL CABINETS**

TEMPERATURE CONTROL		B 9025	B 9051	B 9130	B 9420
Variation	+ / - °C	0,2	0,2	0,2	0,2
Deviation (spatial)	+ / - %	1	1	1,5	1,5
Readability / Setability	°C	0,1/0,1	0,1/0,1	0,1/0,1	0,1/0,1
Range	°C	t <sub>b</sub> -99,9	t <sub>b</sub> -99,9	t <sub>b</sub> -99,9	t <sub>b</sub> -99,9
Sensor thermocouple "K"		Yes	Yes	Yes	Yes
Controller		PID	PID	PID	PID
Display		LCD	LCD	LCD	LCD

**TIMER**

Standard hours/minutes		99h/59m	99h/59m	99h/59m	99h/59m
Real time program *		Yes	Yes	Yes	Yes

**SAFETY**

Alarm flashing / Acoustic		Yes	Yes	Yes	Yes
Alarm limit settable	°C	Yes	Yes	Yes	Yes
Automatic safety setting	°C	Yes	Yes	Yes	Yes

**FEATURES**

Fan speed steps		1/10	1/10	1/10	1/10
Door gasket silicone		Yes	Yes	Yes	Yes
Glass innerdoor		Yes	Yes	Yes	Yes
Data port, Serial USB		Yes	Yes	Yes	Yes
Pot free alarm, output		Yes	Yes	Yes	Yes

**SHELVES**

Standard / Max	pcs	2/7	2/8	3/16	3/23
Dimensions W x D	mm	346 x 235	434 x 325	534 x 325	602 x 570
Max load pr shelf	kg	20	20	20	30
Permitted total load	kg	50	50	70	100

**HEATING**

Heating up time to 37°C	mins	27	30	33	30
Heat transfer at 70°C	W	65	75	90	190

**POWER**

Nominal Power	W	480	480	930	1430
Nominal voltage	V	230,1~	230,1~	230,1~	230,1~
Frequency	Hz	50/60	50/60	50/60	50/60

**DIMENSIONS**

Exterior W x D x H	mm	490 x 480 x 500	580 x 575 x 550	680 x 675 x 750	753 x 845 x 1360
Interior W x D x H	mm	350 x 255 x 300	440 x 345 x 350	540 x 455 x 555	610 x 600 x 1180
Volume	litres	25	51	130	420

**WEIGHTS / VOLUME**

Net weight	kg	20	35	52	120
Shipping weight	kg	25	40	60	140
Shipping volume	dm <sup>3</sup>	0,21	350	558	1280

t<sub>b</sub> = 2°C ABOVE AMBIENT

\* CAN BE SET AT TWO TEMPERATURES, DAILY OR WEEKLY